

ScreedBoard® 30

The **Ultimate** Acoustic Overlay Board for Concrete Separating Floors



Product Information

ScreedBoard® 30 composite acoustic overlay treatment is designed specifically for concrete separating floors. The board's high density and superior compressive strength resilient layer provides outstanding acoustic performance and is an ideal base to accept a multitude of floor finishes.

Product Benefits

- ⬢ Looks and feels like screed
- ⬢ Compatible with all types of concrete floors
- ⬢ **Robust Detail FFT4** compliant acoustic treatment
- ⬢ Interlocking edge detail
- ⬢ Accepts all types of floor coverings, inc. brittle finishes

Technical Data

ScreedBoard® 30		
Product description	-	Composite acoustic overlay floorboard
Thickness	mm	30
Facing board	-	20mm ScreedBoard 20 (interlocking, HD gypsum)
Resilient layer	-	10mm FIBREfon 10 high load acoustic board
Edge profile	-	Interlocking tongue & groove
Board dimensions	mm	600 x 1200
Weight	kg/m² kg/board	27.20 19.58
Associated flanking strip options	-	YELOfon FS15, 30, 50



Third Party Accreditation and Approvals



Environmental Credentials



01634 29-66-77



collecta.co.uk



technical@collecta.co.uk