

Resilient layers for UFH & ScreedBoard 20 applications

FIBREfon® 8,10 & RUBBERfon® 8

High Performance Resilient Layers for Under Floor Heating & ScreedBoard 20 Applications



| | | FIBREfon | | RUBBERfon |
|-------------------------|------------------------------|--|---|---|
| | | 8* | 10 | 8 |
| Product description | - | Ultimate acoustic performance resilient layer | Resilient layer for concrete floor applications | High compressive strength resilient layer |
| Thickness | mm | 8 | 10 | 8 |
| Composition | - | 70% Recycled polyester fleece | Woodfibre | 100% recycled Re-bonded rubber |
| Board/roll dimensions | m | 0.60 x 1.20 | 0.60 x 1.20 | 1 x 6 |
| Weight | kg/m ² kg/unit | 1.00 0.72 (board) | 2.36 1.70 (board) | 6.00 36.00 (roll) |
| Applications | - | All floor types | Concrete floors | High load areas |
| Robust Detail Compliant | - | FFT4 (E-FS-1, E-FC-1 & E-FC-2) E-FS-3 E-FT-5 E-FT-6 | FFT4 (E-FS-1, E-FC-1 & E-FC-2) | FFT4 (E-FS-1, E-FC-1 & E-FC-2) |


Product Information

To ensure a **ScreedBoard 20** covered underfloor heating system complies with acoustic performance standards **CELLECTA** offers three resilient layers: **FIBREfon 8***, **10** and **RUBBERfon 8**. Each layer provides high levels of isolation, with all three being RD FFT4 compliant.

Product Benefits

- Excellent acoustic performance - All RD FFT 4 compliant
- FIBREfon 8*** proprietary layer for E-FS-3, E-FT-5 & E-FT-6
- Two thickness' available: 8, 10mm
- Easy to cut to size and quick to install

Accreditation and Approvals



Environmental Credentials



Floor Finish Compatibility with Cellecta's Acoustic Treatments

CELLECTA's acoustic treatments can be covered with a multitude of commonly installed floor finishes, including carpet, tiles, luxury vinyl tiles (LVT), vinyl rolls and both engineered and solid wood flooring.

| CELLECTA acoustic treatment | Floor finish | | | | | | | | |
|---|--------------|-----------------------------|------------------------------|--------------------------------|----------------------------|--------------------|----------------------|--------------------------------|---------------------------|
| | Carpet | Carpet Tiles ⁽¹⁾ | Ceramic Tiles ⁽²⁾ | Porcelain Tiles ⁽²⁾ | Stone Tiles ⁽³⁾ | LVT ⁽⁴⁾ | Vinyl ⁽⁴⁾ | Engineered wood ⁽⁵⁾ | Solid Wood ⁽⁵⁾ |
| ScreedBoard 28 | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ |
| ScreedBoard 20 + XFLO + FIBREfon 8 | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ |
| ScreedBoard 20 + XFLO + FIBREfon 10 | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ |
| ScreedBoard 20 + XFLO + RUBBERfon 8 | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ |
| DECKfon 17T, 26T, 30T, 37T, Quattro 39 | ⊕ | ⊕ | | | | ⊖ | ⊖ | ⊕ | ⊕ |
| FIBREfon 12C, 21C, 28C | ⊕ | ⊕ | ⊖ | ⊖ | ⊖ | ⊖ | ⊖ | ⊕ | ⊕ |
| DECKfon Ultramat 15 | ⊕ | | | | | | | ⊖ | ⊖ |
| DECKfon Ultralay 5 | ⊕ | ⊖ | | | | | | ⊕ | ⊕ |
| RUBBERfon Ultratop 3, 5 | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ | ⊕ |
| XFLO Ultraboard 15, 18 | | | ⊕ | ⊕ | ⊕ | | | ⊕ | ⊕ |

Notes. Compatibility of floor finishes is provided as a guide. However, the floor covering manufacturer recommendations must be followed at all times.

- Further preparative measures maybe required when gluing carpet tiles.
- Use appropriate board primer and tile adhesive recommended by the tile manufacture/supplier.
- Use appropriate board primer, tile adhesive and decoupling mat recommended by the tile manufacture/supplier
- Contact manufacturer for suitability and installation advice
- Check with the manufacturer to see if proposed flooring is suitable for UFH applications.

⊕ Suitable

⊖ Contact **CELLECTA** for further advice